

SDS Revision Date: 10/28/2015

1. Identification

1.1. Product identifier

Product IdentityPDQ/Part Number 4405Alternate NamesPDQ/Part Number 4405

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Penetrating Oil.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name The United Oil Company, Inc.

4405 E. Baltimore St. Baltimore, MD 21224

Customer Service: The United Oil Company, Inc. Phone 800.296.1203

Fax 410.592.7149

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor. Muta. 1B;H340 May cause genetic defects.

Carc. 1A;H350 May cause cancer.

Asp. Tox. 1;H304 May be fatal if swallowed and enters airways.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H340 May cause genetic defects.

SDS Revision Date: 10/28/2015



H350 May cause cancer.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P308+313 IF exposed or concerned: Get medical advice / attention.

P331 Do NOT induce vomiting.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Kerosene (petroleum) CAS Number: 0008008-20-6	50 - 75	Asp. Tox. 1;H304	[1][2]
Kerosine (petroleum), hydrodesulfurized; Kerosine- unspecified CAS Number: 0064742-81-0	25 - 50	Asp. Tox. 1;H304	[1]
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified CAS Number: 0064742-70-7	10 - 25	Not Classified	[1]

SDS Revision Date: 10/28/2015



Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified CAS Number: 0064742-52-5	5 - 10	Asp. Tox. 1;H304	[1]
Benzene CAS Number: 0000071-43-2	0.10 - 1.0	Flam. Liq. 2;H225 Carc. 1A;H350 Muta. 1B;H340 STOT RE 1;H372 Asp. Tox. 1;H304 Eye Irrit. 2;H319 Skin Irrit. 2;H315	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

- [1] Substance classified with a health or environmental hazard.
- [2] Substance with a workplace exposure limit.

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and **Eyes**

seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce

vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview Reproductive or genetic defect hazard. Exposure to solvent vapor concentrations from the

> component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatique, muscular weakness, drowsiness and in extreme

cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation

and soreness with possible reversible damage. See section 2 for further details.

Inhalation May be fatal if swallowed and enters airways.

^[3] PBT-substance or vPvB-substance.
*The full texts of the phrases are shown in Section 16.

SDS Revision Date: 10/28/2015



5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO_2 , powder, water spray.

Do not use: water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

None

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

SDS Revision Date: 10/28/2015



7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage. Incompatible materials: Strong oxidizing agents and acids. See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000071-43-2	0000071-43-2 Benzene		[1910.1028] TWA 1 ppm STEL 5 ppm
		ACGIH	TWA: 0.5 ppm STEL: 2.5 ppm Skin, A1, 1
		NIOSH	TWA 0.1 ppm ST 1 ppm
		Supplier	No Established Limit
0008008-20-6	Kerosene (petroleum)	OSHA	No Established Limit
		ACGIH	TWA: 200 mg/m3 Skin, Revised 2003
		NIOSH	TWA 100 mg/m3
		Supplier	No Established Limit
0064742-52-5	064742-52-5 Distillates (petroleum), hydrotreated heavy	OSHA	No Established Limit
naphthenic; Baseoil-unspecified	naphthenic; Baseoil-unspecified	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-70-7	Paraffin oils (petroleum), catalytic	OSHA	No Established Limit
	dewaxed heavy; Baseoil-unspecified		No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-81-0	Kerosine (petroleum), hydrodesulfurized;	OSHA	No Established Limit
Kerosin	Kerosine-unspecified	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000071-43-2	Benzene	OSHA	Select Carcinogen: Yes
		NTP	Known: Yes; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

SDS Revision Date: 10/28/2015



0008008-20-6	Kerosene (petroleum)	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0064742-52-5	Distillates (petroleum),	OSHA	Select Carcinogen: No		
hydrotreated heavy naphthenic; Baseoil-unspecified		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0064742-70-7 Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified		OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0064742-81-0	0064742-81-0 Kerosine (petroleum),		Select Carcinogen: No		
hydrodesulfurized; Kerosine- unspecified		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		

8.2. Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the

appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Not Provided.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance Red Liquid

Odor Mineral spirits odor
Odor threshold Not determined
pH Not Measured
Melting point / freezing point Not Measured
Initial boiling point and boiling range Not Measured

Flash Point 137°F

Evaporation rate (Ether = 1) Not Measured
Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits

Lower Explosive Limit: Not Measured

Upper Explosive Limit: Not Measured

Vapor pressure (Pa)Not MeasuredVapor DensityNot Measured

SDS Revision Date: 10/28/2015



Specific GravityNot MeasuredSolubility in WaterNot MeasuredPartition coefficient n-octanol/water (Log Kow)Not MeasuredAuto-ignition temperatureNot MeasuredDecomposition temperatureNot MeasuredViscosity (cSt)3 cSt

9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Strong oxidizing agents and acids.

10.6. Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Kerosene (petroleum) - (8008-20-6)	2,835.00, Rat - Category: 5	No data available	No data available	No data available	No data available

SDS Revision Date: 10/28/2015



Kerosine (petroleum), hydrodesulfurized; Kerosine- unspecified - (64742-81-0)	No data available	No data available	No data available	No data available	No data available
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified - (64742-70-7)	No data available	No data available	No data available	No data available	No data available
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Benzene - (71-43-2)	2,990.00, Rat - Category: 5	8,263.00, Rabbit - Category: NA	44.70, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity	1B	May cause genetic defects.
Carcinogenicity	1A	May cause cancer.
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard	1	May be fatal if swallowed and enters airways.

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Kerosene (petroleum) - (8008-20-6)	Not Available	Not Available	Not Available
Kerosine (petroleum), hydrodesulfurized; Kerosine- unspecified - (64742-81-0)	Not Available	Not Available	Not Available
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified - (64742-70-7)	Not Available	Not Available	Not Available

SDS Revision Date: 10/28/2015



Distillates (petroleum), hydrotreated heavy naphthenic;	5,000.00, Oncorhynchus	1,000.00, Daphnia	1,000.00 (96 hr), Scenedesmus subspicatus
Baseoil-unspecified - (64742-52-5)	mykiss	magna	
Benzene - (71-43-2)	5.90, Oncorhynchus mykiss	9.20, Daphnia magna	29.00 (72 hr), Pseudokirchneriell a subcapitata

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

Not Provided.

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance Control Act (TSCA)

US EPA Tier II Hazards

All components of this material are either listed or exempt from listing on the TSCA

Inventory.

WHMIS Classification B3 D2A

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

SDS Revision Date: 10/28/2015



EPCRA 313 Toxic Chemicals:

Benzene

Proposition 65 - Carcinogens (>0.0%):

Benzene

Naphthalene

Proposition 65 - Developmental Toxins (>0.0%):

Benzene

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

Benzene

New Jersey RTK Substances (>1%):

Kerosene (petroleum)

Pennsylvania RTK Substances (>1%):

Kerosene (petroleum)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

The information contained herein is furnished without warranty of any kind. The above information is believed to be correct but does not purport to be all inclusive and should be used only as a guide. Users should make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.

End of Document